The Delphion Integrated View

Title: **JP57072272A2: SOLID LITHIUM BATTERY AND ITS MANUFACTURE**

Derwent Title: Lithium solid electrolyte storage battery - has electrolyte thin layer of lithium iodide with high capacitance density [Derwent Record]

Country: **JP** Japan
Kind: **A** (See also: JP63035069B4)

Inventor: **KANDA MOTOI**;
YAMADA SHUJI;

Assignee: **TOSHIBA CORP**
News, Profiles, Stocks and More about this company

Published / Filed: **1982-05-06** / 1980-10-24

Application Number: **JP1980000148364**

IPC Code: **H01M 6/18;** H01M 4/06; H01M 4/50;

Priority Number: 1980-10-24 **JP1980000148364**

Abstract:

PURPOSE: To obtain a battery which has a flat discharge characteristic and small voltage decrease at high voltage by constituting the battery by use of a negative lithium electrode, a positive electrode made of a mixture consisting of manganese dioxide and lithium iodide, and an electrolyte made of a thin lithium-iodide layer produced between the electrodes.

CONSTITUTION: A negative electrode 1 made of lithium metal or its alloy, a positive pellet 2 prepared from a mixture consisting of manganese dioxide and lithium iodide, and a solid electrolyte 3 made of a thin lithium iodide layer produced in the interface between these electrodes joined together are used in constituting a solid battery. For instance, a current collecting body is placed in a metal mold, a mixture consisting of manganese dioxide and lithium iodide is placed on the current collecting body, and the mixture is lightly pressed. A negative lithium-plate electrode and another current collecting body are placed over the former mixture, and a pressure of around 3t/cm2 is applied on the current collecting body. After that, the battery is wired with a lead wire, and the entire battery is covered with paraffin, thus a solid battery is obtained. Consequently, a battery which has a flat discharge characteristic and small voltage decrease at high voltage can be obtained by improving the diffusion of lithium ions contained in the positive electrode.

INPADOC Legal Status: None **Get Now:** Family Legal Status Report

Family: Show [redacted]own family members

Forward References: **Go to Result Set:** Forward references (1)

PDF	Patent	Pub.Date	Inventor	Assignee	Title
	US6586912	2003-07-01	Tsukamoto; Hisashi	Quallion LLC	Method and apparatus for amplitude limiting battery temperature spikes

Other Abstract Info: CHEMABS 097(12)100669W

(19) (11) Publication number: 57072

PATENT ABSTRACTS OF JAPAN

(21) Application number: **55148364**

(22) Application date: **24.10.80**

(51) Intl. Cl.: **H01M 6/18** H01M 4/06

(30) Priority:

(43) Date of application publication: **06.05.82**

(84) Designated contracting states:

(71) Applicant: **TOSHIBA CORP**

(72) Inventor: **KANDA MOTOI**
YAMADA SHUJI

(74) Representative:

(54) SOLID LITHIUM BATTERY AND ITS MANUFACTURE

(57) Abstract:

PURPOSE: To obtain a battery which has a flat discharge characteristic and small voltage decrease at high voltage by constituting the battery by use of a negative lithium electrode, a positive electrode made of a mixture consisting of manganese dioxide and lithium iodide, and an electrolyte made of a thin lithium-iodide layer produced between the electrodes.

CONSTITUTION: A negative electrode 1 made of lithium metal or its alloy, a positive pellet 2 prepared from a mixture consisting of manganese dioxide and lithium iodide, and a solid electrolyte 3 made of a thin lithium iodide layer produced in the interface between these electrodes joined together are used in constituting a solid battery. For instance, a current collecting body is placed in a metal mold, a

mixture consisting of manganese dioxide and lithium iodide is placed on the current collecting body, and the mixture is lightly pressed. A negative lithium-plate electrode and another current collecting body are placed over the former mixture, and a pressure of around 3t/cm2 is applied on the current collecting body. After that, the battery is wired with a lead wire, and the entire battery is covered with paraffin, thus a solid battery is obtained. Consequently, a battery which has a flat discharge characteristic and small voltage decrease at high voltage can be obtained by improving the diffusion of lithium ions contained in the positive electrode.